

VEICHI

VH-IV Series Compact PLC



VEICHI

Suzhou Veichi Electric Co., Ltd

No.1000 Songjia Road, Guoxiang street, Wuzhong

Economic and Technological Development Zone,

Tel: +86-512-6617 1988 Fax: +86-512-6617 3610

Facebook: <https://www.facebook.com/veichigroup>

WhatsApp: +86-138 2881 8903

<https://www.veichi.org/>



Official Website

*Version: Y5/2-08
Veichi Electric Co., Ltd all rights reserved,
subject to change without notice.

Stock Code: 688698

About Us



Veichi Electric (Stock Code: 688698) is a leading high-tech enterprise specializing in R&D, production and sales of industrial automation products. Headquartered in Suzhou with R&D centers in Shenzhen and Xi'an and a subsidiary in India, we serve the global markets with competitive and reliable products and system solutions.


The comprehensive product portfolio - spanning AC drives, servo systems, control systems and digital energy solutions, covers all industrial automation layers—management, control, drive, and execution, which is transforming operations in heavy industries, advanced manufacturing, renewable energy, and medical equipment through smart, scenario-based implementations. Moreover, Veichi is also expanding into robotics, new energy and medical fields with innovative products like coreless motors, frameless motors, PV energy storage inverters and surgical power systems.

With 214 patents (including 56 invention patents) as of December 31, 2024, its core technological competencies encompasses: Advanced Motor Control-Comprehensive solutions including vector control, HF injection, auto-tuning, and high-speed flux-weakening control for both PMSMs and AMs, Next-Generation Power Electronics-Cutting-edge SiC applications and robust IGBT drive protection systems, Intelligent Operation-Innovative fly track technology for smooth

motor startup and reliable V/F scalar control and Thermal Management-High-density water cooling layout solutions for optimal system performance.

These breakthroughs have garnered the company prestigious accreditations from national and provincial authorities, including: Third Batch National Specialized, Sophisticated, Distinctive and Innovative 'Little Giant' Enterprise, National High-Tech Enterprise, Jiangsu Provincial Engineering Technology Research Center, Jiangsu Provincial Enterprise Technology Center, and Jiangsu Industrial Internet Development Demonstration Enterprise (Benchmark Factory Category).

Moving forward, Veichi will uphold the mission of "market-driven innovation and technology-led development," and continue to redouble its commitment to core technology breakthroughs and product upgrades towards high-performance, high-quality, and high-reliability applications, fostering technological progress across the global electrical transmission and industrial control sectors.



Product Profile



VH Series Compact PLC:


This lineup includes the VH100, VH200, VH300, VH500, VH600, and VH series remote modules, covering the applications from small to medium-sized automation control in multi-axis motion control, temperature and other analog control, as well as communication networking. The slim footprint allows more expansion boards and modules to fit in the narrow space without compromise on performance. A variety of industrial network communication protocols are integrated for easier data acquisition with other devices on site. And the programming software is continuously updated with more functions and easy operation in line with the customer needs.

Product Orientation




Note: For details of expansion modules related to VH series products, please refer to P18-P29; for product installation dimensions, please refer to P32.


Product Features



Naming Rules



VH100-0808TN-IV
Economical Type



- Stand-alone PLC
- Narrow scenario application
- Excellent price/performance ratio
- RS-232 and RS-485 communication
- 8×DI and 8×DO
- Small-scale automation application

Product Features

8 × HSC

2×high-spped counting(50kHz)
6×high-spped counting(10kHz)
Single/two-phase(Up/Down) and
AB phase(1x and 4x) counting

Serial Comm Port

1×RS232 and 1×RS485
COM0 and COM1 respectively, up to 115.2K
COM0 for programming port and Modbus RTU slave
COM1 for Modbus RTU master and slave, FreePort and N:N
Built-in termination resistor selected by dip switch

3 × PTO

3×high-speed pulse train output(100kHz)
Positioning control command
group for easy start

USB Port

USB2.0
Common Type-C USB cable-compliant
Quicker firmware upgrade

Slim Structure

24mm in the width for smaller footprint
Plug-in wiring for easy maintenance

Technical Specifications

Item	Specification	
Communication	Interface	2×Asynchronous serial port: COM0 for RS232 and COM1 for RS485. 1×USB interface
	Baud rate	1.2kbps~115.2kbps
	Communication protocol	Modbus/FreePort/N:N
	USB	USB 2.0, Type-C for uploading/downloading/monitoring/firmware update
DI and DO Characteristics	Input type	Sourcing/sinking
	Rated voltage	DC24V, 4mA
	Logic 1 [Voltage range]	> 15VDC
	Logic 0 [Voltage range]	< 5VDC
	Input filter	Digital filter to X0 ~ X7, up to user programs
	Max. leakage current	1mA
	Isolation	2kV capacitor
	High-speed counter	Single-phase: 2×50kHz; 6×10kHz Two-phase: 1×25kHz; 3×5kHz
	Max.pulse output(transistor)	3×100kHz high-speed pulse train output
Common Characteristics	Basic command time	0.2μs
	Program capacity	16k Bytes
	Real-time clock	NO
	Max extension module	NO
	Power-down save	FLASH for permanent save, 2k word elements max
	Power supply	DC24V
	Programming language	Proprietary software AutoStudio with LD, IL and SFC



VH200 Series

General Type

- Lightweight structure with flexible extensions
- I/O and analog extension modules available according to actual requirements
- Up to 16 right-side extension modules.
- EtherNET, RS-232, RS-485, and other communication compatibility
- Some models standard with built-in analog I/O for flexible configuration

Product Features

Flexible Extensions

Slim and compact design with optional right extensions
Analog/digital I/O control modules available for selection

Communication & Connectivity

Built-in 1 × EtherNet, 1 × RS232, and 1 × RS485 for basic communication needs

Built-in Analog I/O

1 × AD and 1 × DA for flexible configuration based on customer requirements

Ultra-Slim Design

24mm in thickness, ideal for space-constrained wiring scenarios
Plug-and-play terminal blocks for easy maintenance

Technical Specifications

Item	VH210-0808TN/P-IV	VH210-0808TN/P1-IV	
Program capacity	32kBytes		
Data capacity	128 kBytes (user soft components) / 32 kBytes (power-off save)		
Local extension	16 right extension modules; left extension cards not supported		
Real-time clock	NO		
Programming language	Proprietary software Auto Studio with LD, FBD, SFC		
Ethernet	Modbus-TCP Master/Slave: Former with 6 slaves max; and latter for 4 masters max. TCP free protocol with 4 connections		
RS485	Terminal resistor	1×isolated RS485 port with terminal resistor; master(up to 31 Modbus-RTU slaves)/slave compatibility	
	Baud rate	1.2 kbps ~115.2 kbps	
	Communication protocol	Modbus/Free Port/N:N	
RS232	1×RS232 USB with baud rate: 1.2 kbps ~ 115.2 kbps		
USB	TYPE-C interface (USB 2.0 Full Speed) for program uploading/downloading, monitoring, and firmware upgrades		
High-speed I/O	Pulse input	2×50 kHz high-speed inputs; 6×10 kHz mid-speed input	
	Pulse output	4×100 kHz high-speed outputs	
Analog specifications	AD input range	NO	1×AI (0mA~20mA)
	AD input accuracy	NO	±1% (full scale, @25°C)
	DA output range	NO	1×AO (0mA~20mA)
	DA output accuracy	NO	±1% (full scale, @25°C)



VH300 Series High-performance Type

- Slim modular design
- Strong performance with dual CPUs of 600M clock speed
- Improved arithmetic processing
- Multi-channel pulse control application
- 16×right extension modules addable
- 1×left extension board for more functions

Product Features

Flexible Extensions

Optional left and right extension boards or modules covering a variety of communication functions and analog/digital I/O control.

Various Comm Interface

1×RS-485 for CANopen and Modbus TCP master/slave
TYPE-C port for debugging and SD card for firmware upgrade


8×PTO/PTI

8×high-speed pulse train input and output
Positioning control command group for easy start


Slim Structure

Vertical structure for smaller footprint
Quick release terminals for faster maintenance
Direct wiring with push-in terminals for tool-free installation

Multiple Motion Control Channels




Linear and Circular Interpolation



2-axis linear and circular interpolation corresponds to the 2-axis XY platform control to realize the accurate positioning of the slide.

Electronic Gear and Cam



Flying Shear: By tracking the progress of the material and setting the cutting length, it can automatically plan the movement trajectory to cut the material at fixed length.

Chasing Shear: Set the starting point and length of the sync zone to determine the allowable travel range of the chasing shear axis and the starting point and end point of the round-trip movement, and plan the cam trajectory curve to realize sync cutting.

Various Motion Control Modes

Single-axis	Speed control Position control Home Torque control
Multiple-axis	Electronic gear Speed sync Electronic cam Position sync Interpolation Multiple-axis interpolation
Others	Rotary cut Easy command for easy operation Probe High speed and high precision capture

Technical Specifications

Item	VH301-0808TN/P-IV	VH311-0808TN/P-IV
Power supply	DC24V	
Program capacity	200K Bytes	
Power-down save	128K bytes for user soft components, about 84k bytes for power-down save 1M bytes for user-defined variables, about 128k bytes for power-down save	
Programming language	Proprietary software AutoStudio with LD, IL and SFC	
Right extension No.	16 modules expandable on the right	
Real-time clock	No real-time clock, expandable on the left	
Left extension	1 board	
SD card	For firmware upgrade	
USB	USB 2.0, Type-C for uploading/downloading/monitoring/firmware update	
I/O	Input	8×high-speed pulse train output(200kHz) for single/two-phase(Up/Down) and AB phase (1x and 4x) counting
	Output	8×high-speed pulse train output(100kHz), and positioning control command group supported
Serial Port	Baud rate	1.2kbps~115.2kbps
	Comm protocol	1×built-in and 2 more expandable on the left for Modbus/FreePort/N:N
	Termination resistor	Built-in, master or slave application, 31 Modbus-RTU slaves max.
CAN	NO	CANopen master with up to 31 slaves
EtherNET	NO	Modbus TCP master/slave for uploading/downloading and monitoring 16 slaves and 4 masters max at the same time.TCP free protocol for 4 connections
Motion control	Positioning control command group, linear and circular interpolation, electronic gear, and electronic cam	



VH500 Series EtherCAT Type

- Slim modular design
- 16×right extension modules and 1× left extension board
- EtherCAT bus control and dual-port network switching
- Process encapsulation and re-application through FB/FC functions
- Multi-level network communication through RS485, Ethernet, CAN and EtherCAT interfaces

Product Features

1G CPU

Substantial increase in command processing speed over previous products for high speed and high precision motion control and stable process control

Multi-level Network

1×RS 485 on the product for CANopen communication, 72 EtherCAT slaves max.
Dual Ethernet ports for easy networking over levels

Bus + Pulse Motion Control

Up to 48 real axes for EtherCAT bus motion control, 64 real and virtual axes in total
8×high-speed pulse input and output(200kHz)

Self-developed Programming Soft

ST in programming to write complex algorithms and logic
Offline debugging and online modification functions to reduce on-site debugging time
Function block encapsulation to quick apply the process algorithms



48-Axis EtherCAT

48-axis high-speed bus control with sync movement for complex production. Fast and precise control for higher end-user benefits.

Simple wiring for lower design and labor cost and quicker maintenance.

Jerk ACC and DEC

Jerk value regulation for smoother ACC/DEC curve and less mechanical shock



x-coordinate: Time
1st Y-coordinate: Speed
2nd Y-coordinate: Acceleration
3rd Y-coordinate: Acceleration change rate

- Change rate of ACC/DEC speed obtained directly from the ACC/DEC time without calculation
- Change rate visualized in the smoothness of the ACC/DEC curves


Real/virtual axes 64	Max real axis EtherCAT buses 48	Max EtherCAT slaves 72
Communication cycle 250 μ s	Sync accuracy ±80 ns	High-speed I/O 8×200 kHz

Advanced industrial Ethernet and distributed master/slave

Easy installation for faster information transfer cycle and faster communication and sync

Linear arc interpolation, cams and other modes available

- Motion network bus EtherCAT with communication cycle as fast as 250 μ s.
- Multi-axis commands such as e-gear and e-cam.
- Single-axis motion commands such as position, speed, and home.
- Main axis for encoder or virtual axis, real axis, external input, etc.
- Servo probe, high-speed counter probe, encoder probe available
- Phase compensation, motion superposition, etc.



Multi-level Network One-stop Control

Technical Specifications

Item	VH511-0808TN/P-IV	VH522-0808TN/P-IV	VH523-0808TN/P-IV	VH524-0808TN/P-IV	
Power supply	DC24V				
Program capacity	200K Bytes				
Power-down save	128K bytes for user soft components, about 84K bytes for power-down save 1M bytes for user-defined variables, about 128K bytes for power-down save				
Programming language	Proprietary software AutoStudio with LD, IL and SFC				
Right extension No.	16				
Real-time clock	No real-time clock, expandable on the left extension				
Left extension	1 board				
SD card	For firmware upgrade				
USB	USB 2.0, Type-C for uploading/downloading/monitoring/firmware update				
I/O	Input	8	8xhigh-speed pulse train output(200kHz) for single/two-phase(Up/Down) and AB phase(1x and 4x) counting		
	Output	8	8xhigh-speed pulse train output(100kHz), and positioning control command group supported		
Serial Port RS-485	Comm port	1xbuilt-in and 2 more expandable on the left for Modbus/FreePort/N/N			
	Termination resistor	Built-in. PLC for master/slave application, 31 Modbus-RTU slaves max.			
CAN	NO	CANopen master with up to 31 slaves			
EtherNET	Port No.	1	2xEthernet ports with shared network board and IP address, network switching supported		
	Protocol	Modbus TCP master/slave for uploading/downloading and monitoring 16 slaves and 4 masters max at the same time. TCP free protocol for 4 connections			
Motion control	Positioning control command group, linear and circular interpolation, electronic gear, and electronic cam				
EtherCAT	Axis No.	8	16	32	48
	Slave No.	72 slaves max(including servo axes), real and visual axes 48 in total			
	Axis performance	Communication cycle in 250µs-8ms			

Programming Software

Self-developed Programming Software

AUTO STUDIO Upgrade Non-stop



Oscilloscope



ST Language



Network Configuration



FB Function Block



Customized Function Block



Offline Simulation



VH600 Series CODESYS-based Medium Controller



This is the first medium-sized PLC independently developed by VEICHI. Based on years of experience in the industrial control development and analysis of actual situations from various cases, this robust medium controller comes out specifically for high-end equipment and factory automation.

It provides users with ultra-high-speed computing and processing, excellent system performance, and a range of integrated functions. So, it is ideal for large-scale automation control of different processes, production lines and the whole factories.

Product Features

Standard Development Platform

Full conformity to IEC61131-3 and PLCopen specification.
Diversified programming languages (LD, FBD, ST, SFC, CFC)
Customized function library encapsulation
Integrated with rich motion control libraries, mathematical models, etc. for rapid development

Multi-level Network

2×EtherNet (shared IP, built-in switch) 2×EtherCAT for up to 128 slaves.
Sync cycle for 8 axes in 1ms, 16 axes in 2ms
EtherNet/IP(master/salve)
ModbusTCP(master/salve)
3×RS485, each for 50 slaves 16×OPCUA client connection
CANopen communication for 31 slaves

Modular Free Configuration


16 modules expandable on the right
Analog I/O, digital I/O, RS485, RCT clock optional on the left
SD card for upgrade

Fast and Precise Motion Control

8×high-speed counting input(200K) and 8×high-speed pulse output(200K)
Complex control functions such as single-axis/multi-axis movement, interpolation, electronic cams and electronic gears, G-code, robots, etc.


Standard Programming

- CODESYS-based programming in full conformity to IEC61131-3
- Diversified programming languages of ST, FBD, CFC, SFC and LD




Convenient Programming

- Online program modification, breakpoint tuning, and single-step cycle for enhanced efficiency
- Perfect error diagnosis function with TRACE function to monitor the movement track and locate the fault
- Powerful project management covering multi-task and multi-device download to deal with large-scale projects



Motion Control

- Multi-core processors assignment, Multicore 4 Cores supported
- Faster command processing and response, 8-axis sync cycle under bus control as fast as in 1ms.
- Single/multi-axis commands such as e-gear and e-cam Linear, circular, and axis combination interpolation
- Robot motion control, customized motion models, visualization functions, OPC UA functions, etc. available for complex and diverse scenarios




Rich Motion Library

- Motion control libraries in conformity to PLCOpen specifications
- User-defined encapsulation of function libraries and function blocks available
- Motion control libraries, robot libraries, customized kinematics and mathematical models integrated



Extensive Standard Industrial Network



VH600-0808TN-IV Specifications

Item	Specification			
Model	VH600-0808TN/P-IV	VH601-0808TN/P-IV	VH602-0808TN/P-IV	VH603-0808TN/P-IV
Axis No.	128 axes max	8	16	32
Rated voltage	DC24V			
RS485	1×RS485			
CAN	CANOpen master with up to 31 slaves			
EtherNet	2×EtherNet(built-in switch) for ModbusTCP, and program upload/download			
EtherCAT	128 EtherCAT slaves max. (including servo axes)			
High speed input	8×200K			
High speed output	8×200K, sourcing/sinking for option			
Left extension	2×RS485 expandable			
Right extension	16 max.			
SD card	1×32G SD card			
Data capacity	10MB for programs, and 512kb for power-down save (Flash),20MB for data			
Language	LD, FBD, IL, ST, SFC, CFC in conformity to IEC 61131-3 Programming Language			
Motion control	Linear and circular interpolation, electronic gear, and electronic cam			





VTC Series

Temperature Controller

- A new-generation multi-channel high-precision temperature control product
- 8×high-speed, high-accuracy sampling and multi-loop PID regulation
- Suitable for various temperature control applications
- Compatible with thermocouples and RTDs for high measurement accuracy
- Integrated multi-channel digital output with rich functionality for user convenience

Product Features

Dedicated Debugging Software

Proprietary self-developed PC software for easy user configuration

Multi-channel Temperature Control

Integrated multi-channel temperature control with centralized data management in the PC software


Convenient Communication

Supports RS485 and USB communication, enabling seamless data exchange between the temperature controller and other devices or PC software

Precision Control


Auto-tuning and multi-segment temperature setting functions ensure high-precision temperature control

Naming Rules



Specifications

Item	VTC-0408MT-IV		VTC-0808TT-IV
AI	Thermocouple	K, J, E, N, T, R, S, B	
	RTD	PT100, PT1000, Cu100, JPt100, Cu50, Ni120	NO
DO	Output type	8×NPN, loop supply voltage: 5V~24V, loop current: 0.3A/24VDC	
	Response time	<0.5ms	
Sampling cycle	Depends on valid input and control channels, min. 60ms, max. 400ms		
Control cycle	Depends on control object, min. 100ms		
Control mode	PID control, ON/OFF control, manual control		
Temperature measurement range	-200°C~1800°C		
Rated temperature range	K-type	-120°C ~ 1360°C	
	J-type	-90°C ~ 1190°C	
	E-type	-70°C ~ 990°C	
	N-type	-200°C ~ 1290°C	
	T-type	-140°C ~ 390°C	
	R-type	-40°C ~ 1750°C	
	S-type	-40°C ~ 1750°C	
	B-type	60°C ~ 1800°C	
	Pt100	-190°C ~ 650°C	NO
	JPT100	-190°C ~ 650°C	NO
	PT1000	-190°C ~ 300°C	NO
	Cu100	-40°C ~ 140°C	NO
	Cu50	-40°C ~ 140°C	NO
Ni120	-60°C ~ 290°C	NO	
Accuracy	Thermocouple	±0.3% of full scale, ambient temperature compensation error ≤2°C	
	RTD	±0.5% of input range	
Isolation	Isolation between sampling channels and power supply and between sampling channels and outputs		



VH Series Remote Extension Module

- Compact & lightweight design for easy integration
- Rapid signal processing with microsecond-level response
- Plug-and-Play installation and assembly
- Robust performance for harsh environments
- Optimized for standard fieldbus systems
- Modular design including communication interface module (master/host link) and extension modules (flexible I/O extension)
- Scalable configuration for lower wiring and hardware expenses
- Customizable setup of communication modules and extensions to site needs
- Distributed control ideal for decentralized automation with centralized management

Free Configuration

Stable Performance

Easy operation

Product Features



16×modules max.



New generation of bus speeds up to 100Mbps



Cabinet space reduced by 2/3



D-BUS design
Metal plate fitted on both sides for higher reliability

VH-RTU-ECT-IV (EtherCAT Master Communication)

Item	Specification
Extension No.	16 in total, including IO and special modules
Backplane bus	VBUS, VEICHI-defined
Backplane speed	100M
Transfer cycle	125 μs min.
Backplane bus compatibility	Remote modules compatible with local module communication protocols
Backplane communication	Daisy-chain fast-forwarding mode
EtherCAT port	IN: EtherCAT input OUT: EtherCAT output for EtherCAT slaves
Rated input voltage	24V DC (20.4V DC~ 28.8V DC)
Rated input current	0.6A (typical at 24V)
Power output derating	Derate 85% at 55°C
Isolation	24V not isolated from DO/DI, while DO/DI isolated from AO/AI
Power protection	Overcurrent protection, anti-reverse connection protection, and surge absorption
Input PDO No.	1024 bytes max.
Output PDO No.	1024 bytes max.
Input mailbox	256 bytes max.
Output mailbox	256 bytes max.
IO mapping	Three IO mapping methods: bit access, byte access, and word access
Stop output mode	Output according to fault stop mode and preset value, no more refresh



VH-RTU-PN-IV (PROFINET Master Communication)

Item	Specification
Communication mode	RT mode
Min.transfer cycle	1ms
I&M data	I&M0-I&M3
PROFINET version	V2.3
Extension No.	16 modules max.
PROFINET port	2
PROFINET switch	Networking supported
Physical layer	100BASE-TX
Traffic rate	100 Mbit/s (PROFINET)
Communication	Full duplex
Topology	Line, star, and tree type
Transmission medium	Cat5e and above
Transmission distance	<100m between two nodes
Prioritized startup	YES
Port disable	YES
Reconfiguration after replacement	NO(PN module of the same kind)
Factory reset	YES
Extension factory reset	NO
Firmware upgrade	YES



VH-RTU-DP-IV (PROFIBUS DP Master Communication)

Item	Specification
Physical layer	RS485
Communication rate	12 Mbit/s (PROFIBUS)
Communication mode	Half-duplex
Topology	Daisy-chain
Transmission medium	Shielded twisted pair
Transmission distance	< 100m between two nodes
Extension capacity	Up to 16 in total, including I/O modules and certain special modules
Backplane bus	VBUS (VEICHI-defined)
Backplane speed	100M
Backplane bus compatibility	Remote modules and local modules communication protocols compatible
Backplane communication mode	Daisy-chain fast-forwarding mode
PROFIBUS interface	DB9
I/O mapping	Bit access, byte access, and word access (three I/O mapping modes)



VH Series Right Extension Module

- VH200, VH300, VH500, VH600 and VH series communication module compatibility
- 16×right extension modules addable for all
- New generation of bus speed up to 100Mbps

Product Features

 Status diagnostics indicators for quick checks
Colored plates for quick I/O function checks
Clearly codes on wiring

 D-BUS connectors
Corrosion-resistant connector materials
Better stability than SMD design

 Removable terminals
Convenient terminals for module replacement without rewiring

 Large terminal diameter for higher cable compatibility
Push-in terminals for higher wiring efficiency

DI Module Specifications

Item	Specification	Model	Specification
Input method	Sourcing/sinking selectable via "S/S" terminal (except the Input/output hybrid module)	VH-1600END-IV	16×DI module
Isolation	Comes with the module	VH-0800END-IV	8×DI module
Input voltage	24V DC	VH-0808ETN-IV	8×DI module, sinking 8×NPN DO module
Input current	4mA(Typical)	VH-0808ETP-IV	8×DI module, sourcing 8×PNP DO module
Input impedance	6k(reference)		
ON voltage	>15V DC		
OFF voltage	<5V DC		
Response time	1ms		
Software filter time	(0~255) *0.25μs		
Operating temperature	-20°C~55°C		
Bus power rated current	100mA (Typical at 5V DC)		
Module hot swap	NO		

VH-4AD-IV Module Specifications

Item	Specification
Input type	AI
Isolation	Capacitor isolation between analog and digital circuits Internal isolation between analog circuit and module 24V DC power No isolation between analog channels
Input method	Voltage/current
Input channel	4
Resolution	16-bit
Switching time	60μs/channel
Voltage range	±10V, 0V~10VV, ±5V, 0V~5V, 1V~5V
Voltage impedance	1MΩ
Voltage accuracy (25°C)	±0.1% (full-scale)
Voltage limit	±12V
Voltage diagnosis	No disconnection detection
Current range	±20mA, 0mA~20mA, 4mA~20mA
Current sampling impedance	250Ω
Current accuracy (25°C)	±0.1%(full-scale)
Voltage limit	±30mA for instantaneous range, ±24mA avg.
Current diagnosis	Disconnection detection on under 4mA~20mA
Operating temperature	-20°C~55°C
Bus power rated current	120mA (Typical at 5V DC)
Module hot swap	NO

DO Module Specifications

Item	Specification	Model	Specification
Output mode	Sourcing or sinking for different models	VH-0016ETN-IV	16×NPN DO
Isolation	Optocoupler-isolated	VH-0016ETP-IV	16×PNP DO
Output voltage	24V DC	VH-0008ETN-IV	8×NPN DO
Output load (Resistance)	0.5A/terminal, 2A/module	VH-0008ETP-IV	8×PNP DO
Output load (Inductance)	7.2W/terminal,12W/module	VH-0808ETN-IV	8×DI module, sinking 8×NPN DO module
Output load (Lamp)	5W/terminal, 9W/module	VH-0808ETP-IV	8×DI module, sourcing 8×PNP DO module
Response time	100μs		
Indicator	Indicator lights up when the optocoupler works		
Leakage current under open circuit	<0.1Ma/30V DC		
Min. load	5mA (5V ~ 24Vdc)		
Protections	Short circuit protection		
Operating temperature	-20°C~55°C		
Bus power rated current	100mA (Typical at 5V DC)		
Module hot swap	NO		

VH-4DA-IV Module Specifications

Item	Specification
Output type	AO
Isolation	Communication between analog and digital circuits isolated by capacitors Internal isolation between analog circuit and module 24V DC power No isolation between analog channels
Output method	Voltage/current
Output channel	4
Resolution	12-bit
Switching time	250μs/channel
Voltage range	±10V, 0V~10V, ±5V, 0V~5V, 1V~5V
Voltage impedance	1KΩ
Voltage accuracy (25°C)	±1% (full-scale)
Voltage diagnosis	No short circuit detection
Current range	0mA~20mA, 4mA~20mA
Current sampling impedance	0Ω~600Ω
Current accuracy (25°C)	±1% (full-scale)
Current diagnosis	No open circuit detection
Bus power rated current	80mA (Typical at 5V DC)
Module hot swap	NO

VH-4PT-IV Module Specifications

Item	Specification			
	Celsius (°C)		Fahrenheit (°F)	
Input signal	PT100, PT500, PT1000, Cu50, Cu100, KTY84, NTC5K, NTC10K, 4 channels in total			
Resolution	24-bit			
Slew rate	(15±2%) ms × 4 channels (unused channels not converted)			
Rated temperature	PT100/500/1000	-150.0°C ~ 600.0°C	PT100/500/1000	-238.0°F ~ 1112.0°F
	Cu100/Cu50	-30°C ~ 120°C	Cu100/Cu50	-22°F ~ 248°F
	KTY84	0.0°C ~ 200.0°C	KTY84	32.0°F ~ 392.0°F
	NTC5K/10K	-30.0°C/-25°C ~ +200.0°C	NTC5K/10K	-22.0°F/-13°F ~ 392.0°F
Sensitivity	0.1°C		0.1°F	
Accuracy (25°C)	Full scale*±0.1%			
Accuracy (-20°C~+55°C)	Full scale*±0.3%			
Isolation	Communication between analog and digital circuits isolated by capacitors Internal isolation between analog circuit and module 24V DC power ; No isolation between analog channels			
Bus power rated voltage	5V DC (4.75V~5.25V DC)			
Bus power rated current	120mA (Typical at 5V DC)			
Module hot swap	NO			

VH-2WT-IV Module Specifications

Item	Specification
Channel No.	2
Isolation	Unified Isolation (No isolation between channels)
Resolution	24-bit
Digital range	32-bit
Conversion speed	150 SPS, 300 SPS, 450 SPS (Configurable per channel)
Bridge measurement (Rated)	±39mV
Reference measurement (Rated)	5V
Sensor sensitivity	0V/V~6mV/V
Load capacity	40 Ω~4010 Ω
Calibration method	Manual calibration, copy calibration parameters
Hardware filter	Low-pass filter (below 10 kHz)
Software filter	Power frequency filter, moving average filter
Weighing accuracy	0.01%

VH-4TC-IV Module Specifications

Item	Specification			
	Celsius (°C)		Fahrenheit (°F)	
I/O occupancy	No			
Input signal	Thermocouples: Types K, J, E, B, N, T, R, S for channels, 4 channels in total			
Resolution	24-bit			
Slew rate	(240±2%)ms × 4 channels (unused channels not converted)			
Compensation method	Cold junction compensation			
Rated temperature	Type K	-100°C ~ 1200°C	Type K	-148°F ~ 2192°F
	Type J	-100°C ~ 1000°C	Type J	-148°F ~ 1832°F
	Type E	-100.0°C ~ 1000°C	Type E	-148°F ~ 1832°F
	Type B	200°C ~ 1800°C	Type B	392°F ~ 3272.°F
	Type N	-100°C ~ 1200°C	Type N	-148°F ~ 2192°F
	Type T	-200°C ~ 400°C	Type T	-328°F ~ 752°F
	Type R	0°C ~ 1600°C	Type R	32°F ~ 2912°F
	Type S	0°C ~ 1600°C	Type S	32°F ~ 2912°F
Sensitivity	0.1°C		0.1°F	
Accuracy (25°C)	(±0.1%) (±100mV full scale) + cold junction compensation error			
Accuracy (-20°C~+55°C)	(±0.3%) (±100mV full scale) + cold junction compensation error			
Isolation	Communication between analog and digital circuits isolated by capacitors DC/DC isolation between the analog circuit power supply and the 24Vdc power supply			
Bus power rated voltage	5V DC (4.75V~5.25V DC)			
Bus power rated current	120mA (Typical at 5V DC)			
Module hot swap	NO			

Note: With appropriate mode settings, both °C and °F data can be obtained.

VH Series Left Extension Module



VH300, VH500, VH600 Series
One expansion board to the left for all

VH-RS485(-RTC)-IV

Item		Specification
RS485	Channel No.	2
	Isolation	YES
	Termination resistor	Controlled by a dip switch, connected by default
	Slave No.	Up to 31 slaves (VH600 for 50 slaves), the distance between each slave <3m.
	Baud rate	9.6 kbit/s, 19.2 kbit/s, 38.4 kbit/s, 57.6 kbit/s, 115.2 kbit/s
	Distance	<100m for 115.2kbit/s <1000m for 19.2kbit/s

VH-2AD1DA-V/I-(RTC)-IV

Item	Input	Output
Channel No.	2	1
Voltage range	0V ~ 10V	
Current range	0mA ~ 20mA	
Voltage input impedance/output load	> 200kΩ	> 2kΩ
Current sampling impedance/output load	250Ω	<500Ω
Slew rate	2ms/channel	
Input accuracy (25°C)	Voltage ±1%, current ±1% (full-scale)	±1% (full-scale)
Input accuracy (full temperature scale)	Voltage ±3%, current ±3% (full-scale)	±5% (full-scale)
Resolution	12bit	
Digital Output	0 ~ 10000	




VH-4DI-(RTC)-IV

Item	Specification	
Input type	DI	
Input channel	4	
Input method	Sourcing and sinking	
Input voltage level	24V DC±10% (21.6V~26.4V DC)	
Common input	Current when input ON	> 2.5mA
	Current when input OFF	< 1mA
	Response time	≈10ms(RC filter time)
Input impedance	6kΩ	
ON voltage	≥15V DC	
OFF voltage	≤5V DC	
Software filter time	NO	
Isolation	Optocoupler isolated	
Public terminal	One public terminal shared by 4 inputs (Input power supply polarity +/- changeable)	
Input display	Indicator ON during input (controlled by hardware)	



VH-4DO-TN-(RTC)-IV

Item	Specification	
Output type	Digital transistor low side output	
Output channel	4	
Voltage level	24V DC (21.6V DC~26.4V DC)	
Common output	Output load (Resistance)	0.5A/terminal, 1A/Public terminal
	Output load (Inductance)	6W/24V DC
	Output load (Lamp)	1W/24V DC
	Hardware response time ON/ OFF	≤100μs (OFF→ON and ON→OFF)
	Load current	≥5mA
	Max. output frequency	Resistance load 100Hz, inductance load 0.5Hz, lamp load 10Hz
OFF leakage current	<50μA	
Max. ON residual voltage	<0.5V DC	
Isolation	Optocoupler isolated	
Public terminal	One public terminal shared by 4 inputs(Output power -)	
Surge suppressor	Zener diode	
Short circuit protection	NO	
Output display	Indicator ON during output (controlled by hardware)	



VH-RTC-IV

Item	Specification
Communication	PC
Clock accuracy	120 seconds/month
Clock format	Year-Month-Day Hour-Minute-Second
Battery	CR2354-corded coin cell battery, 5 years life, replaceable




VH Series Main Module Models

Type	Model	Input	Output	Type-C	Serial Port	CANopen	Ethernet	EtherCAT
General Medium-sized PLC	VH600-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	128 axes max.
	VH600-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	128 axes max.
	VH601-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	8 axes max.
	VH601-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	8 axes max.
	VH602-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	16 axes max.
	VH602-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	16 axes max.
Motion Control PLC	VH603-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	32 axes max.
	VH603-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	32 axes max.
	VH524-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	48 axes max.
	VH524-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	48 axes max.
	VH523-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	32 axes max.
	VH523-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	32 axes max.
High-performance PLC	VH522-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	16 axes max.
	VH522-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Dual	16 axes max.
	VH511-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	NO	Single	8 axes max.
	VH511-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	NO	Single	8 axes max.
	VH311-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	Master	Single	NO
	VH311-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	Master	Single	NO
General PLC	VH301-0808TN-IV	8×200kHz	8×NPN(200kHz)	Program download	1×RS485, expandable on left	NO	NO	NO
	VH301-0808TP-IV	8×200kHz	8×PNP(200kHz)	Program download	1×RS485, expandable on left	NO	NO	NO
	VH210-0808TN1-IV	2×50kHz, 6×Medium-speed,1×AD	4×NPN(100kHz),1×DA	Program download	1×RS485, 1×RS232	NO	Single	NO
	VH210-0808TP1-IV	2×50kHz, 6×Medium-speed,1×AD	4×NPN(100kHz),1×DA	Program download	1×RS485, 1×RS232	NO	Single	NO
	VH210-0808TN-IV	2×50kHz, 6×Medium-speed	4×NPN(100kHz)	Program download	1×RS485, 1×RS232	NO	Single	NO
	VH210-0808TP-IV	2×50kHz, 6×Medium-speed	4×PNP(100kHz)	Program download	1×RS485, 1×RS232	NO	Single	NO
Economical PLC	VH100-0808TN-IV	2×50kHz, 6×Medium-speed	3×NPN(100kHz)	Program download	1×RS485, 1×RS232	NO	NO	NO
	VH100-0808TP-IV	2×50kHz, 6×Medium-speed	3×PNP(100kHz)	Program download	1×RS485, 1×RS232	NO	NO	NO
Temperature Controller	VTC-0408MT-IV	4×PT/TC	8×NPN	Program download	1×RS485	NO	NO	NO
	VTC-0808TT-IV	8×TC	8×NPN	Program download	1×RS485	NO	NO	NO
Remote Communication	VH-RTU-ECT-IV	EtherCAT remote communication interface modules		Message reading	NO	NO	NO	Slave
	VH-RTU-PN-IV	PROFINET remote communication interface modules		Message reading	NO	NO	NO	NO
	VH-RTU-DP-IV	Profibus DP remote communication interface modules		Message reading	NO	NO	NO	NO

Left Extension Models

Model	Specification
VH-RS485-1-IV	1×RS485
VH-RS485-IV	2×RS485
VH-RS485-RTC-1-IV	1×RS485 + Real-Time Clock (RTC)
VH-RS485-RTC-IV	2×RS485 + Real-Time Clock (RTC)
VH-ADI-IV	4×DI
VH-ADI-RTC-IV	4×DI + Real-Time Clock (RTC)
VH-ADO-TN-RTC-IV	4×Sinking Digital Output + Real-Time Clock (RTC)
VH-2AD1DA-I-IV	2×AI, 1×AO(Current Type)
VH-2AD1DA-I-RTC-IV	2×AI, 1×AO (Current Type) + RTC
VH-2AD1DA-V-IV	2×AI, 1×AO (Voltage Type)
VH-2AD1DA-V-RTC-IV	2×AI, 1×AO (Voltage Type) + RTC
VH-RTC-IV	Real-Time Clock Extension Board




Right Extension Models

Model	Specification
VH-1600END-IV	16×DI
VH-0800END-IV	8×DI
VH-0016ETN-IV	16×NPN DO
VH-0016ETP-IV	16×PNP DO
VH-0808ETN-IV	8×DI+ 8×NPN DO
VH-0808ETP-IV	8×DI+ 8×PNP DO
VH-0008ETN-IV	8×NPN DO
VH-0008ETP-IV	8×PNP DO
VH-4AD-IV	4×AI
VH-4DA-IV	4×AO
VH-4DA2-IV	4×AO (0.1% Accuracy)
VH-4PT-IV	4×RTD (Resistance Temperature Detector) Input
VH-4TC-IV	4×Thermocouple Input
VH-2WT-IV	2×Weighing Input




Installation Dimensions(mm)


VH100/200/VTC




VH-RTU



VH300/500/600



VH Right Extension



Research and Production

R&D and Technology Platform

- > Consolidating a dynamic force of top-tier professionals and technical experts in domestic industrial control, our R&D team represents 37.16% of our workforce, with 74.62% of our technical staff boasting bachelor's degrees or higher.
- > Guided by philosophy of "Innovate with technology and strive for excellence," VEICHI is deeply customer-centric by providing stable and reliable products and technologies designed to the evolving needs of our clients.
- > Investing 10% of our revenue into R&D, VEICHI has crafted advanced labs for EMC, safety, reliability, and performance testing to ensure product quality.
- > In-depth cooperation with many famous universities and research institutions in China has been established and "Jiangsu Postdoctoral Innovation Practice Base" and "Jiangsu Postgraduate Workstation" are set up successively.

Intelligent Automation

- > Digitally driven from inception to production, VEICHI boasts an annual capacity of 914,600 units with streamlined efficiency.
- > 5 imported SMT placement lines, 5 automated coating lines, 4 DIP test lines, a robotic arm-equipped automated line, and 12 production lines are equipped with the latest intelligent manufacturing tools.
- > All of the product checks are carried out automatically by the management mode of 3 (tri-inspection system)+ 1(proportional inspection) during the whole process for standard performance.
- > Three major production management system WMS, MES and ERP together ensure that the unique code of each product is traceable in the system to manage product quality.



Service and Support

